



QC 080000
 IECQ HSPM
 Registered Firm
 有害物质流程管理
 系统验证通过工厂
 (申请中)

PhuizerZinc
一般锌花镀锌钢品
PhuizerZero
无锌花镀锌钢品

| 产品名称 Product Name | 制品规格 Specification | 双面镀层量 Coating Mass on Both Sides | 附注 Remarks |
|--|--|--|--|
| 一般锌花 镀锌钢板 Regular Spangle Hot-Dip Galvanized Steel Sheet- PhuizerZinc | JIS G3302-1998 热轧底板 Hot Rolled Base Metal 一般用 SGHC Commercial 结构用 SGH 340,400, Structural 440,490, 570 冷轧底板 Cold Rolled Base Metal 一般用 SGCC Commercial 一般用、硬板 SGCH Commercial,Hard 冲压用、第一级 SGCD1 Drawing, Class1 冲压用、第二级 SGCD2 Drawing, Class2 冲压用、第三级 SGCD3 Drawing, Class3 结构用、第三级 SGC 340,400, Structural 440,490, 570 | 双面等镀: Equivalent coating 80  350 g/m ² | 表面精整 冷轧底材热浸镀锌钢卷 可实施调质轧延,以得 平滑表面 Surface Finish The coated surface can be skin-passed if required to obtain an extra-smooth surface for cold-rolled base hot-dip galvanized steel sheet. |
| | 无锌花 镀锌钢板 Zero Spangle Hot-Dip Galvanized Steel Sheet- PhuizerZero | ASTM A653M-2000 一般品质 Commercial Steel CS Type A B C 扣锁成型品质 Forming Steel FS Type A B 深冲品质 Deep Drawing Steel DDS 超深冲品质 Extra Deep Drawing Steel EDDS 结构品质 Structural Steel Grade 230 255 275 340 550 | 双面等镀: Equivalent coating 80  350 g/m ² |

炸辉(中国) 镀锌钢品

| 产品名称 Product Name | 制造方法 Manufacturing Process | 特性 Characteristics | 用途 Typical Applications | 表面状况 Surface Aspect |
|--|--|---|--|--|
| 一般锌花 镀锌钢板 Regular Spangle Hot-Dip Galvanized Steel Sheet- PhuizerZinc | 钢板自镀锌槽升起,镀 层以正常方式凝固产生 锌花。 Strip emerged from the galvanizing bath, the spangles result from the unrestricted growth of zinc crystals during normal solidification. | 1. 锌花大而明显。 2. 耐蚀性佳。 1. Bright appearance and well-developed zinc spangle. 2. Good corrosion resistance. | ■ 建筑材料:楼承板、天花板、 风管工程、屋顶、隔间、仓库、 筒仓、轻量型钢。 ■ 运输工业:车体配板、油箱。 ■ 其他:大型谷仓、电线导管、 道路护栏、脚手架。 ■ Construction: Decks , ceiling , ducts ,roofing ,partitions , warehouse ,silo ,purlin ■ Transportation : Automotive part , oil tank. ■ Others: Barn , conduits , guardrail , scaffold. |  |
| 无锌花 镀锌钢板 Zero Spangle Hot-Dip Galvanized Steel Sheet- PhuizerZero | 1. 镀锌层尚未凝固前 利用锌花细微化设备 以锌粉吹射,控制锌 花结晶,形成极细小 锌花。 Zinc powder blown on the molten zinc layer acts as nucleation sites for minispangle 2. 或控制槽成分及锌 固化冷却速率,以获得 极细小锌花。 Or the zinc crystal growth is inhibited by a combination of coating-bath chemistry plus cooling during solidification of the zinc. | 1. 涂漆后表面均匀美观。 2. 可供应薄镀层之镀锌 板易于焊接。 3. 耐蚀性佳。 1. Homogeneous and beautiful surface after painting. 2. Provide thin zinc coating for easy welding. 3. Good corrosion resistance. | ■ 建筑材料:铁卷门、天花板 支架、窗框。 ■ 家电制品:洗衣机、电冰箱、 冷气机。 ■ 其它:日光灯件,自动贩卖机, 车体内部配件,电脑外壳。 ■ Construction : shutter ,suspension bar for ceiling ,framing. ■ Electrical appliance: Washing machine, refrigerator, air-conditioner. ■ Other : Lighting fixture ,vending machine ,automotive parts, computer case. |  |



炸辉(中国)厂
 地址:江苏省常熟市经济开发区沿江工业区炸辉路1号
 总机: +86-512-52298888
 邮编: 215536
 营业专线: +86-512-52298414
 技术服务专线: +86-512-52298122
 WEBSITE: <http://www.yiehphuichina.com>
 E-mail: sales@yiehphuichina.com

经销商/Distributor